STRIKER-X "AMBER + WHITE"



STRIKER-X WIRING INSTRUCTIONS	
BLACK (THICK)	Apply to Negative for Ground
RED (THICK)	Apply to +12-24VDC Constant Positive (Fused)
PURPLE	Apply to Positive to Activate AMBER Warning Modules
BROWN	Apply to Positive to Activate WHITE Warning Modules
PURPLE + BROWN	Apply to Positive for Combination Warning of AMBER and WHITE Warning
BLUE	Apply Momentarily to Positive for Pattern Change
ORANGE	Apply to Positive to DISABLE Rear Facing WHITE Modules
WHITE	Apply to Positive for Night Mode Dimming to 70% Brightness

"STEADY-ON" WORK LIGHT FUNCTIONS	
RED	Apply to Positive for LEFT Alley Spot Light *Steady-On* WHITE
GREEN	Apply to Positive for RIGHT Alley Spot Light *Steady-On* WHITE
BLACK	Apply to Positive for FRONT Take Down Spot Lights *Steady-On* WHITE
YELLOW	Apply to Positive for FRONT Super Take Down Flood Lights *Steady-On* WHITE

TRAFFIC DIRECTIONAL ARROW FUNCTIONS		
PINK	Apply to Positive for LEFT Rearward Traffic Directional Arrow AMBER	
GREY	Apply to Positive for RIGHT Rearward Traffic Directional Arrow AMBER	
PINK + GREY	Apply to Positive for SPLIT Rearward Traffic Directional Arrow AMBER	